

ITEM	ABBR.	DESCRIPTION
	-	RECTANGULAR DUCT
	-	ROUND DUCT
	-	45 ° TAP - USE AT BRANCH DUCTS ONLY
	-	CURVED (LONG SWEEP) DUCT ELBOW MINIMUM RADIUS R=1.5 x WIDTH
	-	90 ° RECTANGULAR DUCT ELBOW WITH SINGLE RADIUS TURNING VANES
	FD	FIRE DAMPER - COMBO FIRE / SMOKE DAMPER
	OBD	BALANCING DAMPER (USE O B.D. UNLESS NOTED OTHERWISE)
	-	SPIN-IN DUCT TAKE-OFF W/ DAMPER
	SA	SUPPLY AIR DUCT
	EXH	EXHAUST AIR DUCT
	RA	RETURN AIR DUCT
	TSTAT	THERMOSTAT
	RTS	REMOTE TEMPERATURE SENSOR
	HS	REMOTE HUMIDITY/TEMPERATURE SENSOR
	NH	NEXREV EMS HUMIDITY SENSOR
	NT	NEXREV EMS TEMPERATURE SENSOR
	BP	BUILDING PRESSURE SENSOR
	-	OPEN-ENDED DUCT
	-	1-WAY THROW SUPPLY AIR DIFFUSER
	-	2-WAY THROW SUPPLY AIR DIFFUSER
	-	2-WAY THROW SUPPLY AIR DIFFUSER
	-	3-WAY THROW SUPPLY AIR DIFFUSER
	-	4-WAY THROW SUPPLY AIR DIFFUSER
	-	RETURN AIR GRILLE
	-	EXHAUST GRILLE
	-	AIR DEVICE DESIGNATION
	-	MECHANICAL/PLUMBING EQUIPMENT DESIGNATION
	-	SPOT ELEVATION, MEASURED FROM BOTTOM OF DUCT

